



Product # V-1201

14/2 In-Wall

14 gauge 2 conductor speaker cable, featuring 41 strand oxygen-free copper (OFC) conductors and ripcord. General Purpose (CL3) fire safety rating for installation in walls and risers (between floors) in residential buildings and in walls in commercial buildings. UL Listed.

<https://www.voltive.com/products/voltive-14-2-speaker-wire>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	General Purpose (CL3)
Flame Test	UL 1685
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.45mm ± 0.08mm
Minimum Thickness	0.36mm
Outer Diameter	2.70mm ± 0.20mm
Resistance	≥ 100 megaohms/km
Dielectric Strength	500V AC for 1 minute

Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1201-1	V-1085	Black	500ft	Box	850001725859	23.7 lbs	13.9 x 10.2 x 13.5	View
V-1201-3		White	100ft	Spool	810095240553	4.7 lbs	7.9 x 7.9 x 3.5	View
V-1201-2	V-1075	White	500ft	Box	850001725637	23.7 lbs	13.9 x 10.2 x 13.5	View

Conductors

Gauge	14AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	1.86mm
Strand Count	41
Strand Diameter	0.251mm
DC Resistance	≤ 8.60 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness	0.50mm ± 0.08mm
Minimum Thickness	0.34mm
Outer Diameter	6.40mm ± 0.30mm
Minimum Bend Radius	15 x diameter (96mm)
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 14AWG 2C - E516774-XX (UL) CL3 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1201 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING