



Product # V-1203

16/4 In-Wall

16 gauge 4 conductor speaker cable, featuring 26 strand oxygen-free copper (OFC) conductors and ripcord. General Purpose (CL3) fire safety rating for installation in walls and risers (between floors) in residential buildings and in walls in commercial buildings. UL Listed.

<https://www.voltive.com/products/voltive-16-4-speaker-wire>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	General Purpose (CL3)
Flame Test	UL 1685
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black, White, Green
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.30mm ± 0.08mm
Minimum Thickness	0.24mm
Outer Diameter	2.10mm ± 0.20mm
Resistance	≥ 100 megaohms/km
Dielectric Strength	500V AC for 1 minute

Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1203-1		Black	500ft	Box	810095240652	27.3 lbs	13.9 x 10.2 x 13.5	View
V-1203-2	V-1002	White	500ft	Box	850001725187	27.3 lbs	13.9 x 10.2 x 13.5	View

Conductors

Gauge	16AWG
Count	4
Material	Oxygen Free Copper
Outer Diameter	1.46mm
Strand Count	26
Strand Diameter	0.251mm
DC Resistance	≤ 13.70 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness	0.50mm ± 0.08mm
Minimum Thickness	0.34mm
Outer Diameter	6.20mm ± 0.30mm
Minimum Bend Radius	15 x diameter (93mm)
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 16AWG 4C - E516774-XX (UL) CL3 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1203 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING