



Product # V-1205

10/2 In-Wall + Direct Burial

Premium 10 gauge 2 conductor speaker cable, featuring 105 strand oxygen-free copper (OFC) conductors, quick-strip sleeve, ripcord, and a super-luxe outer jacket. Direct Burial rated for underground installation without conduit. General Purpose (CL3) fire safety rating for installation in walls and risers (between floors) in residential buildings and in walls in commercial buildings. UL Listed.

<https://www.voltive.com/products/voltive-10-2-max-speaker-wire>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	General Purpose (CL3)
Flame Test	UL 1685
Testing Laboratory	UL
Direct Burial?	Yes
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.50mm ± 0.08mm
Minimum Thickness	0.40mm
Outer Diameter	4.00mm ± 0.20mm
Resistance	≥ 100 megaohms/km
Dielectric Strength	500V AC for 1 minute

Conductors

Gauge	10AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	2.97mm
Strand Count	105
Strand Diameter	0.251mm
DC Resistance	≤ 3.41 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness	0.90mm ± 0.10mm
Minimum Thickness	0.64mm
Outer Diameter	10.00mm ± 0.30mm
Minimum Bend Radius	15 × diameter (150mm)
Paper Tissue?	Yes
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 10AWG 2C - E516774-XX (UL) CL3 DIRECT BURIAL 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1205 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING

Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1205-1	V-1003	Black	100ft	Spool	850001725286	10.5 lbs	7.9 x 7.9 x 6.6	View
V-1205-3	V-1005	Black	250ft	Box	850001725118	27.9 lbs	13.9 x 10.2 x 13.5	View
V-1205-5	V-1007	Black	500ft	Spool	850001725309	55.1 lbs	13.8 x 13.8 x 9.8	View
V-1205-2	V-1004	White	100ft	Spool	850001725293	10.5 lbs	7.9 x 7.9 x 6.6	View
V-1205-4	V-1006	White	250ft	Box	850001725101	27.9 lbs	13.9 x 10.2 x 13.5	View
V-1205-6	V-1008	White	500ft	Spool	850001725620	55.1 lbs	13.8 x 13.8 x 9.8	View