



Product # V-1215

14/2 Plenum

14 gauge 2 conductor speaker cable, featuring 41 strand oxygen-free copper (OFC) conductors and ripcord. Plenum (CL3P) fire safety rating for installation in walls, risers (between floors), and plenums in both residential and commercial applications. UL Listed.

<https://www.voltive.com/products/voltive-14-2-plenum-speaker-wire>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Plenum (CL3P)
Flame Test	NFPA 262
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Low-smoke Flame Retardant Polyvinyl Chloride (LSFRPVC)
Average Thickness	0.32mm ± 0.08mm
Minimum Thickness	0.26mm
Outer Diameter	2.53mm ± 0.20mm
Resistance	≥ 100 megaohms/km
Dielectric Strength	500V AC for 1 minute

Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1215-1	V-1045	Black	500ft	Box	850001725156	22.0 lbs	13.9 x 10.2 x 13.5	View
V-1215-3		White	100ft	Spool	810095240706	4.3 lbs	6.3 x 6.3 x 3.5	View
V-1215-2	V-1046	White	500ft	Box	850001725071	22.0 lbs	13.9 x 10.2 x 13.5	View

Conductors

Gauge	14AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	1.86mm
Strand Count	41
Strand Diameter	0.251mm
DC Resistance	≤ 8.60 ohms/km

Jacket

Available Colors	Black, White
Material	Low-smoke Flame Retardant Polyvinyl Chloride (LSFRPVC)
Thickness	0.38mm ± 0.05mm
Minimum Thickness	0.26mm
Outer Diameter	5.80mm ± 0.20mm
Minimum Bend Radius	20 x diameter (116mm)
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 14AWG 2C - E516774-XX (UL) CL3P 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1215 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING