



Product # V-1223

## 22/2 Stranded In-Wall

22 gauge 2 conductor stranded alarm wire, featuring 7 strand oxygen-free copper (OFC) conductors and ripcord. General Purpose (CL3) fire safety rating for installation in walls and risers (between floors) in residential buildings and in walls in commercial buildings. UL Listed.

<https://www.voltive.com/products/voltive-22-2-stranded-alarm-wire>

### Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	General Purpose (CL3)
Flame Test	UL 1685
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

### Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.20mm ± 0.05mm
Minimum Thickness	0.15mm
Outer Diameter	1.15mm ± 0.10mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	2500V AC for 1 minute

### Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1223-1	V-1082	White	500ft	Coilpack	850001725736	4.5 lbs	11.0 x 11.0 x 2.8	<a href="#">View</a>

### Conductors

Gauge	22AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	0.75mm
Strand Count	7
Strand Diameter	0.250mm
DC Resistance	≤ 55.40 ohms/km

### Jacket

Available Colors	White
Material	Polyvinyl Chloride (PVC)
Thickness	0.45mm ± 0.10mm
Minimum Thickness	0.35mm
Outer Diameter	3.30mm ± 0.30mm
Minimum Bend Radius	20 x diameter (66mm)
Ripcord	Cotton
Printing	VOLTIVE 22AWG 2C - V-1223 - (UL) CL3 E516774-XX 75C - MM/YY - XXX-XXX - XXX FT USED / XXX FT REMAINING