


Specifications & Technical Data



Revision: 1.0, Date: 2024-06-24



Product # V-1258

22/2 Shielded Riser

22 gauge 2 conductor shielded wire for alarm, audio, or control, featuring 7 strand oxygen-free copper (OFC) conductors and ripcord. Riser (CL3R) fire safety rating for installation in walls and risers (between floors) in both residential and commercial buildings. UL Listed.

<https://www.voltive.com/products/V-1258>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Riser (CL3R)
Flame Test	UL 1666
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.20mm ± 0.05mm
Minimum Thickness	0.15mm
Outer Diameter	1.15mm ± 0.10mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Shielding

Material	Aluminum & Mylar foil
Drain Wire?	Yes

Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1258-2		Black	500ft	Box	810095241154	8.3 lbs	10.8 x 8.6 x 9.8	View
V-1258-1		White	500ft	Box	810095241161	8.3 lbs	10.8 x 8.6 x 9.8	View

Conductors

Gauge	22AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	0.75mm
Strand Count	7
Strand Diameter	0.250mm
DC Resistance	≤ 55.40 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness	0.58mm ± 0.10mm
Minimum Thickness	0.48mm
Outer Diameter	3.80mm ± 0.30mm
Minimum Bend Radius	10 x diameter (38mm)
Ripcord	Cotton
Printing	VOLTIVE 22AWG 2C SHIELDED - V-1258 - (UL) CL3R E516774-XX 75C - MM/YY - XXX-XXX - XXX FT USED / XXX FT REMAINING