


Specifications & Technical Data

Revision: 1.0, Date: 2024-06-24



Product # V-1262

14/2 Shielded Riser

14 gauge 2 conductor shielded wire for alarm, audio, or control, featuring 41 strand oxygen-free copper (OFC) conductors and ripcord. Riser (CL3R) fire safety rating for installation in walls and risers (between floors) in both residential and commercial buildings. UL Listed.

<https://www.voltive.com/products/V-1262>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Riser (CL3R)
Flame Test	UL 1666
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.45mm ± 0.08mm
Minimum Thickness	0.36mm
Outer Diameter	2.70mm ± 0.20mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Shielding

Material	Aluminum & Mylar foil
Drain Wire?	Yes

Part Numbers

Part #	Old Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1262-1		White	500ft	Box	810095241048	24.7 lbs	13.9 x 10.2 x 13.5	View

Conductors

Gauge	14AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	1.86mm
Strand Count	41
Strand Diameter	0.250mm
DC Resistance	≤ 8.60 ohms/km

Jacket

Available Colors	White
Material	Polyvinyl Chloride (PVC)
Thickness	0.52mm ± 0.17mm
Minimum Thickness	0.42mm
Outer Diameter	6.80mm ± 0.50mm
Minimum Bend Radius	10 × diameter (68mm)
Ripcord	Cotton
Printing	VOLTIVE 14AWG 2C SHIELDED - V-1262 - (UL) CL3R E516774-XX 75C - MM/YY - XXX-XXX - XXX FT USED / XXX FT REMAINING