



Product # V-1273

## 16/4 Riser

16 gauge 4 conductor speaker cable, featuring 26 strand oxygen-free copper (OFC) conductors and ripcord. Riser (CL3R) fire safety rating for installation in walls and risers (between floors) in both residential and commercial buildings. UL Listed.

<https://www.voltive.com/products/V-1273>

### Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Riser (CL3R)
Flame Test	UL 1666
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

### Insulation

Colors	Red, Black, White, Green
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.35mm ± 0.05mm
Minimum Thickness	0.25mm
Outer Diameter	2.20mm ± 0.20mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

### Conductors

Gauge	16AWG
Count	4
Material	Oxygen Free Copper
Outer Diameter	1.47mm
Strand Count	26
Strand Diameter	0.250mm
DC Resistance	≤ 13.70 ohms/km

### Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness	0.50mm ± 0.05mm
Minimum Thickness	0.40mm
Outer Diameter	6.30mm ± 0.50mm
Minimum Bend Radius	6 × diameter (38mm)
Ripcord	Cotton
Printing	VOLTIVE 16AWG 4C - V-1273 - (UL) CL3R E516774-XX 75C - MM/YY - XXX- XXX - XXX FT USED / XXX FT REMAINING

### Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1273-1	Black	500ft	Box	810095241390	27.3 lbs	13.9 x 10.2 x 13.5	<a href="#">View</a>
V-1273-2	White	500ft	Box	810095241406	27.3 lbs	13.9 x 10.2 x 13.5	<a href="#">View</a>