



Product # V-1274

18/2 Riser

18 gauge 2 conductor wire for alarm, audio, control, or other low voltage systems, featuring 16 strand oxygen-free copper (OFC) conductors and ripcord. Riser (CL3R) fire safety rating for installation in walls and risers (between floors) in both residential and commercial buildings. UL Listed.

<https://www.voltive.com/products/V-1274>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Riser (CL3R)
Flame Test	UL 1666
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.30mm ± 0.05mm
Minimum Thickness	0.22mm
Outer Diameter	1.80mm ± 0.20mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1274-1	Black	500ft	Box	810095241413	11.4 lbs	11.6 x 9.9 x 11.8	View
V-1274-2	White	500ft	Box	810095241420	11.4 lbs	11.6 x 9.9 x 11.8	View

Conductors

Gauge	18AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	1.15mm
Strand Count	16
Strand Diameter	0.250mm
DC Resistance	≤ 21.90 ohms/km

Jacket

Available Colors	Black, White
Material	Polyvinyl Chloride (PVC)
Thickness	0.40mm ± 0.05mm
Minimum Thickness	0.35mm
Outer Diameter	4.20mm ± 0.50mm
Minimum Bend Radius	6 × diameter (25mm)
Ripcord	Cotton
Printing	VOLTIVE 18AWG 2C - V-1274 - (UL) CL3R E516774-XX 75C - MM/YY - XXX- XXX - XXX FT USED / XXX FT REMAINING