



Product # V-1278

12/2 Shielded Riser

12 gauge 2 conductor shielded wire for alarm, audio, control, or other low voltage systems, featuring 65 strand oxygen-free copper (OFC) conductors and ripcord. Riser (CL3R) fire safety rating for installation in walls and risers (between floors) in both residential and commercial buildings. UL Listed.

<https://www.voltive.com/products/V-1278>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Riser (CL3R)
Flame Test	UL 1666
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.40mm ± 0.05mm
Minimum Thickness	0.32mm
Outer Diameter	3.20mm ± 0.10mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Shielding

Material	Aluminum & Mylar foil
Drain Wire?	Yes

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1278-1	White	500ft	Box	810095241475	37.5 lbs	16.5 x 10.2 x 15.9	View

Conductors

Gauge	12AWG
Count	2
Material	Oxygen Free Copper
Outer Diameter	2.32mm
Strand Count	65
Strand Diameter	0.250mm
DC Resistance	≤ 5.41 ohms/km

Jacket

Available Colors	White
Material	Polyvinyl Chloride (PVC)
Thickness	0.60mm ± 0.05mm
Minimum Thickness	0.48mm
Outer Diameter	7.40mm ± 0.50mm
Minimum Bend Radius	12 × diameter (89mm)
Ripcord	Cotton
Printing	VOLTIVE 12AWG 2C SHIELDED - V-1278 - (UL) CL3R E516774-XX 75C - MM/YY - XXX-XXX - XXX FT USED / XXX FT REMAINING