



Product # V-1306

20/4 Shielded Riser

20 gauge 4 conductor shielded wire for alarm, audio, control, or other low voltage systems, featuring 7 strand oxygen-free copper (OFC) conductors and ripcord. Riser (CL3R) fire safety rating for installation in walls and risers (between floors) in both residential and commercial buildings. UL Listed.

<https://www.voltive.com/products/V-1306>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Riser (CL3R)
Flame Test	UL 1666
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black, White, Green
Material	Polyvinyl Chloride (PVC)
Average Thickness	0.20mm ± 0.08mm
Minimum Thickness	0.16mm
Outer Diameter	1.36mm ± 0.10mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Shielding

Material	Aluminum & Mylar foil
Drain Wire?	Yes

Conductors

Gauge	20AWG
Count	4
Material	Oxygen Free Copper
Outer Diameter	0.94mm
Strand Count	7
Strand Diameter	0.314mm
DC Resistance	≤ 34.40 ohms/km

Jacket

Available Colors	White
Material	Polyvinyl Chloride (PVC)
Thickness	0.40mm ± 0.10mm
Minimum Thickness	0.32mm
Outer Diameter	4.18mm ± 0.30mm
Minimum Bend Radius	15 × diameter (63mm)
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 20AWG 4C SHIELDED - E516774-XX (UL) CL3R 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1306 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1306-1	White	500ft	Box	810095241987	11.7 lbs	11.6 x 9.9 x 11.8	View