




Product # V-1310

16/4 Shielded Plenum

16 gauge 4 conductor shielded wire for alarm, audio, control, or other low voltage systems, featuring 26 strand oxygen-free copper (OFC) conductors and ripcord. Plenum (CL3P) fire safety rating for installation in walls, risers (between floors), and plenums in both residential and commercial applications. UL Listed.

<https://www.voltive.com/products/V-1310>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Plenum (CL3P)
Flame Test	NFPA 262
Testing Laboratory	UL
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black, White, Green
Material	Low-smoke Flame Retardant Polyvinyl Chloride (LSFRPVC)
Average Thickness	0.28mm ± 0.08mm
Minimum Thickness	0.22mm
Outer Diameter	2.10mm ± 0.20mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Shielding

Material	Aluminum & Mylar foil
Drain Wire?	Yes

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1310-1	White	500ft	Box	810095241802	24.4 lbs	13.9 x 10.2 x 13.5	View

Conductors

Gauge	16AWG
Count	4
Material	Oxygen Free Copper
Outer Diameter	1.46mm
Strand Count	26
Strand Diameter	0.251mm
DC Resistance	≤ 13.70 ohms/km

Jacket

Available Colors	White
Material	Low-smoke Flame Retardant Polyvinyl Chloride (LSFRPVC)
Thickness	0.38mm ± 0.05mm
Minimum Thickness	0.26mm
Outer Diameter	6.10mm ± 0.20mm
Minimum Bend Radius	20 x diameter (122mm)
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 16AWG 4C SHIELDED - E516774-XX (UL) CL3P 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1310 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING