


Specifications & Technical Data

Revision: 1.1, Date: 2026-07-02

VOLTIVE



Product # V-1333

14/2 Shielded Plenum

14 gauge 2 conductor shielded cable for alarm, audio, control, LED lighting, or other low voltage systems, featuring 41 strand bare copper conductors and ripcord. Plenum (CL3P) fire safety rating for installation in walls, risers (between floors), and plenums in both residential and commercial applications. UL Listed.

<https://www.voltive.com/products/V-1333>

Standards & Ratings

Voltage Rating	300V
Temperature Rating	75°C
Materials & Construction	UL 13
Fire Rating	Plenum (CL3P)
Flame Test	NFPA 262
Testing Laboratory	UL
Wet Location?	No
Direct Burial?	No
Sunlight Resistant?	No
RoHS?	Yes

Insulation

Colors	Red, Black
Material	Low-smoke Flame Retardant Polyvinyl Chloride (LSFRPVC)
Average Thickness	0.32mm ± 0.08mm
Minimum Thickness	0.26mm
Outer Diameter	2.53mm ± 0.20mm
Resistance	≥ 50 megaohms/km
Dielectric Strength	500V AC for 1 minute

Shielding

Material	Aluminum & Mylar foil
Drain Wire?	Yes

Part Numbers

Part #	Color	Length	Packaging	UPC	Weight	L x W x H (in)	Link
V-1333-1	White	500ft	Box	810095242557	19.7 lbs	13.9 x 10.2 x 13.5	View

Conductors

Gauge	14AWG
Count	2
Material	Bare Copper
Outer Diameter	1.86mm
Strand Count	41
Strand Diameter	0.251mm
DC Resistance	≤ 8.60 ohms/km

Jacket

Available Colors	White
Material	Low-smoke Flame Retardant Polyvinyl Chloride (LSFRPVC)
Thickness	0.38mm ± 0.05mm
Minimum Thickness	0.26mm
Outer Diameter	5.92mm ± 0.20mm
Minimum Bend Radius	20 × diameter (118mm)
Ripcord	Nylon (1000D)
Printing A	VOLTIVE 14AWG 2C SHIELDED - E516774-XX (UL) CL3P 75C - XXX FT USED / XXX FT REMAINING
Printing B	V-1333 - MM/YY - XXX-XXX - VOLTIVE.COM - XXX FT USED / XXX FT REMAINING